

**UNCLASSIFIED**

---

**AD 295 811**

*Reproduced  
by the*

**ARMED SERVICES TECHNICAL INFORMATION AGENCY  
ARLINGTON HALL STATION  
ARLINGTON 12, VIRGINIA**



---

**UNCLASSIFIED**

**NOTICE:** When government or other drawings, specifications or other data are used for any purpose other than in connection with a definitely related government procurement operation, the U. S. Government thereby incurs no responsibility, nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use or sell any patented invention that may in any way be related thereto.

62-1646

295 811

SPECIAL RECTIFIERS

By

V. G. Ulitin

ASTIA  
RECEIVED  
FEB 11 1963  
RECEIVED  
TISIA

295811

# UNEDITED ROUGH DRAFT TRANSLATION

## SPECIAL RECTIFIERS

By: V. G. Ulitin

English Pages: 2

Source: Byulleten' Tekhniko-Ekonomicheskoy  
Informatsii, No. 3, pp. 23-24, 1962.

SC-1621  
SOV/193-62-0-3-2/5

THIS TRANSLATION IS A RENDERING OF THE ORIGINAL FOREIGN TEXT WITHOUT ANY ANALYTICAL OR EDITORIAL COMMENT. STATEMENTS OR THEORIES ADVOCATED OR IMPLIED ARE THOSE OF THE SOURCE AND DO NOT NECESSARILY REFLECT THE POSITION OR OPINION OF THE FOREIGN TECHNOLOGY DIVISION.

PREPARED BY:

TRANSLATION SERVICES BRANCH  
FOREIGN TECHNOLOGY DIVISION  
DT-APB, ONR.

FTD-TT-62-1646-1+4

Date 21 Jan. 19 63

P

## SPECIAL RECTIFIERS

V. G. Ulitin

The Dnepropetrovsk mining-automation plant has begun the production of the VSK-300\*, universal welding rectifier, the VS-600 welding rectifier, and the VS-2M rectifier-regulator.

The VS-600 welding rectifier is designed for welding in a medium of protective gases and under flux. The rectifier power is supplied by a 380 volt, 50 cycle, three-phase line. The input power is about 30 kw.

The primary winding of the transformer is tapped for step-by-step regulation of the secondary voltage. The selenium rectifier unit is connected in a three-phase double-half period rectification bridge circuit. A smoothing choke is connected to the bridge output.

The rectified welding current of the VS-600 goes up to 600 amp, the rectified voltage is 20-40 volts, and there are 27 stages of regulation.

The VS-2M rectifier-regulator is designed for the conversion of a-c current into d-c current regulated by a voltage of 80 to 27 volts.

---

\* Byulleten' Tekhniko-Ekonomicheskoy Informatsiy, No. 12, 1960, p. 18.

This current supplies the electrohygrometers VP-4, VP-4M, VE-2 and VE-2M, which are used in the laboratories of bread-collecting points and at plants of the procurement system. The over-all dimensions of the rectifier are 210 × 140 × 140 mm and the weight is 3 kg.

The VS-2M is supplied by a 127/220 volt, 50 cycle a-c line. The input power does not exceed 35 watts. The rectifier unit is made up of D7V germanium diodes in a bridge circuit. Regulation of the output rectified voltage is accomplished by type SG3S gas-discharge regulators. The apparatus is adjusted for a rectified voltage of 80 and 27 volts by means of an adjustable resistor.

Industrial testing of experimental models of the VSK-300, VS-600 and VS-2M rectifiers has shown good results. Serial production of this equipment is planned for 1962.

# DISTRIBUTION LIST

DEPARTMENT OF DEFENSE	Nr. Copies	MAJOR AIR COMMANDS	Nr. Copies
		AFSC	
		SCFTR	1
		ASTIA	25
HEADQUARTERS USAF		TD-B1a	5
		TD-B1b	3
AFCIN-3D2	1	SSD (SSF)	2
ARL (ARB)	1	APGC (PGF)	1
		ESD (ESY)	1
		RADC (RAY)	1
		AFMTC (MTW)	1
OTHER AGENCIES			
CIA	1		
NSA	6		
AID	2		
OTS	2		
AEC	2		
PWS	1		
NASA	1		
RAND	1		